

125Khz card door access control system with software management and SDK PY-SCR100

Introdction:

SCR100 is an access control devices produced by HF&CCTV, which is made with elegant design and professional surface treatment. The device have lock control, alarm, exit button, door sensor. The wiegand-

in interface is used to connect external reader to construct master and slave system. Also the device can be used to connect with a control panel as a reader by wiegand-

out interface. The operation can be done on PC software and upload to the device through TCP/IP, RS232/485 communication. The USB-

host is used for data download and upload, including user data and record etc. SCR100 is suitable for house, small office and factory etc.

Fetures:

1. Elegant design with Acrylic plastic
2. Revolutionary products in industry with TCP/IP interface, avoid RS485 communication and low speed for transferring data, standalone or network deployment
3. Protect the data with encrypted technology
4. Professional access control function: 50 time zones, 5 groups, 10 open door combination, support multi users entry
5. Built-in relay contacts lock, alarm, door sensor & exit button .
6. Wiegand input&output enable Master/Slaver access control .
7. Embedded webserver: support browser to inquire access data at local or remote .
8. No LCD and no keypad enhance the functions of waterproof
9. Professional access control software for management.

Specifications:

B
D
c
a
r
d
C
a
p
a
c
i
t
y

5
0
a
n
s
a
c
t
i
o
n
C
a
p
a
c
i
t
y
C
O
M
M
U
N
I
C
A
T
I
O
N
/4
8
5
,
U
S
B
-
H
o
s
t

A
c
c
e
p
t
a
r
C
o
n
t
r
i
b
u
t
i
o
n
s
e
n
s
o
r
,
e
x
i
t
b
u
t
t
o
n
,
a
l
a
r
m
,
D
o
o
r
B
e
l
l

W
u
e
g
a
n
&
l
s
p
g
n
a
l
s
h
a
n
d
p
a
d
s
b
a
o
k
t
i
W
e
b
s
e
r
v
e
r
,
g
d
i
g
i
t
a
l
n
u
m
b
e
r

Optimal Functions
Display Web
DCS Supply
Operational
Engineering
Temperature

Wiring diagram:

