time attendance with Camera Wifi PY-iclock2800

Parameters:

Display/Speaker	8 inch TFT touch screen
Speaker: Voice Prompt	Multi-language support
Technical Specifications Capacity	Environment
Fingerprint capacity:8,000	Operation temperature: 0°C ~ 45°C
Log capacity: 200,000	Operation humidity: 20% ~ 80%
Verification speed(1:1): ≤1s	FRR: ≤0.1%
dentification speed(1:N): ≤2s	FAR: ≤0.0001%
Power: 12VDC 1.5A	256.5(L)*79(W)*314.5(H)mm
Communication	Camera
TCP/IP, RS232/485, USB-host	Build-in
Standard Function	Hardware Platform
Norkcode, SMS, DLST, Scheduled-bell, Self-Service Query, Automatic Status Switch, T9 input, ID	card, photo-ID, Backup Battery, web-server ZEM800
	Customize Function(Optional)
	IC Card/,9 digit user ID, Wi-Fi, GPRS, Printer, SOAP
DEM	Yes
5DK	Available
Multi languages	Available
pell scheduling	Built in
Serial and Ethernet ports	Build in

Application: home, office, school, government, building, or other purpose

Wifi time attendance Time attendance distributo, Finger access control Time attendance distributor