

# Face and Fingerprint Recognition rfid Time Attendance System PY-iface800

## Parameters:

CPU	Branded Multi-Bio CPU 800 MHz
Memory	256M Flash, 64M SDRAM
Hardware Platform	ZEM800 Multi-Medium Development Platform
Fingerprint Sensor	Branded Optical Fingerprint Sensor without film
Camera	High Resolution Infrared Camera
Display	4.3" TFT touch screen
Face capacity	1200(1:N)
Fingerprint capacity	2000
Logs capacity	100,000
Algorithm Version	Branded Face 7.0 & Branded Finger 10.0
2000mAh backup battery	Optional
Communication	TCP/IP,RS232/485
USB-HOST	Two USB-Host
Wireless Wi-Fi	Optional
Time attendance Standard functions	ID Card (Optional) , Automatic Status Switch, Self-Service Query, Work Code, T9 input, 9 digit user ID, DLST
Access control interfaces for	3rd party electric lock, door sensor, exit button
Wiegand Signal	Output
OEM	Yes
SDK	Available
<i>Multi languages</i>	Available
bell scheduling	Built in
Serial and Ethernet ports	Build in
Optional functions	serial printer, IC card, Extendable Scheduledbell, Short Massage, Web-server,GPRS,WIFI
Power supply	12V3A
Verification Speed	≤2 sec
Operating temp	0°C- 45 °C

## [rfid access control system](#)

Application: home, office, school, government, building , or other purpose



