

access control time attendance S700

[time attendance system china](#)

Parameters:

| | |
|--|---|
| Display/Speaker | Language |
| LCD Display: 3 TFT touch LCD | Multi Language, English, French, Spanish, Arabic, |
| Speaker: Voice Prompt (language can be selected) | etc., for more than 40 languages can be selected |
| Technical Specifications Capacity | Environment |
| Card capacity: 30,000 | Operation temperature: 0°C ~ 45°C |
| Log capacity: 50,000 | Operation humidity: 20% ~ 80% |
| Verification/Identification | Verification/Identification |
| Verification speed(1:1): ≤0.5s | FRR: ≤0.01% |
| Identification speed(1:N): ≤1s | FAR: ≤0.0001% |
| Communication | Attendance status |
| TCP/IP, USB Host | Check in, Check out, Break in, Break out, OT in, OT out |
| Function Support | Customize Function |
| Auto status, DST; SMS, T9 input, 9 User ID, Photo-ID; Multi-verify | rf card reader, , webserver, FLASH disk |
| Power Supply | Machine Size |
| Power: 110/220VAC ~ 12VDC (PS-3A is optional) | 250(L)*150(W)*90(H)mm |
| Access Mode | Access Control |
| Card, PIN, Card+PIN | built-in relay, 50 time zones, 5 groups and 10 combinations; 3rd electric lock, Door sensor, Exit button, Alarm |

Application: home, office, school, government, building , or other purpose.



