

face recognition time attendance and access control PY-iface302

OEM	Yes
SDK	Available
Multi languages	Available
bell scheduling	Built in
Serial and Ethernet ports	Build in

Parameters

Display/Speaker

LCD Display: 4.3" TFT Touch screen
Speaker: Voice Prompt (language can be selected)

Technical Specifications Capacity

Face capacity: 1200; Card capacity: 10,000
Log capacity: 100,000

Verification/Identification

Verification speed(1:1): ≤1s
Identification speed(1:N): ≤1s

Power Supply

Power: 110/220VAC – 12VDC

Communication

TCP/IP, RS232/485, USB Host*2, Wiegand out

Standard Function

High definition infrared camera; 6 user-defines function keys; Built-in relay, simple access control, door sensor; Dismantlement alarm, break-in alarm, duress alarm; Scheduled bell, Workcode, SMS, T9 input, DST, Self inquiry, Photo-ID, Extendable scheduled bell, Webserver, Li-battery, 14-pin code, Printer output, MIFARE reader, WiFi, GPRS

Language

Multi Language, English, French, Spanish, Arabic, etc., for more than 40 languages can be selected

Environment

Operation temperature: 0°C – 45°C
Operation humidity: 20% – 80%

Verification/Identification

FRR: ≤0.01%
FAR: ≤0.0001%

Machine Size

194(L)*165(W)*86(H)mm

Attendance status

Check in, Check out, Break in, Break out, OT in, OT out

Customize Function

Application: home, office, school, government, building , or other purpose