face recognition time attendance and access control PY-iface302

OEM	Yes
SDK	Available
M*ulti languages*	Available
bell scheduling	Built in
Serial and Ethernet ports	Build in

Parameters

Display/Speaker
LCD Display: 4.3" TFT Touch screen
Speaker: Voice Prompt (language can be selected)

Language
Multi Language, English, French, Spanish, Arabic,
etc., for more than 40 languages can be selected

Technical Specifications Capacity
Face capacity: 1200; Card capacity: 10,000
Log capacity: 100,000

Environment
Operation temperature: 0℃ ~ 45℃
Operation humidity: 20% ~ 80%

Verification/Identification
Verification speed(1:1): ≤1s
Identification speed(1:N): ≤1s

Verification/Identification
FRR: ≤0.01%
FAR: ≤0.0001%

Power Supply
Power: 110/220VAC ~ 12VDC

Machine Size
194(L)*165(W)*86(H)mm

Communication
TCP/IP, RS232/485, USB Host*2, Wiegand out

Attendance status
Check in, Check out, Break in, Break out, OT in, OT out

Standand Function
High definition infrared camera; 6 user-defines function keys; Built-in relay, simple asccess control, door sensor; Dismantlement alarm, break-in alarm, duress alarm; Scheduled bell, Workcode, SMS, T9 input, DST, Self inquiry, Photo-ID, Extendable scheduled bell.

Customize Function
Webserver, Li-battery, 14-pin code, Printer output, MIFARE reader, WiFi, GPRS

Application: home, office, school, government, building , or other purpose