

## Frameless glass doors up and down power plug lock

### Features:

- \* Low Temperature, safe & Durable
- \* Low Power, Environmental Protection
- \* Special photo electricity control,three steps current application
- \* Long Life with 500000 Operations
- \* MOV Provides Reverse Current Protection
- \* Superior Strength Aluminium Alloy,Solid Stain-less Steel Bolt
- \* Autolock Time Delay: 0,3,6,9sec.
- \* Door statue signal output contact(NC.COM)
- \* Double protection for loading current
- \* Auto-relock if no Action within 5 secs.
- \* Photoelectricity Control,Low Temperature,  
A:The Low Current is Changed immediately;  
B:When door frame doesn't coincide with door leaf ,door leaf against the bolt,then the electric bolt will start the low-power function to bring low temperature.

C:The Photoelectricity Control Technology, prevent the machanical defect.

### Technical Specifications:

|                     |   |
|---------------------|---|
| Place of Origin     | Guangdong, China (Mainland)                       |
| Brand Name          | Proyu   |
| Model Number        | PY-EL8  |
| Fail Safe           | Lock when energized                               |
| Face Plate          | L148xW43xH39(mm)                                  |
| Bolt                | 17mmDIA,stainless steel 13mm throw                |
| Voltage             | DC12V(DC24V)                                      |
| Start Current       | 900mA   |
| Standby Current     | 120mA   |
| Support Grip        | 400kg   |
| Suitable For        | 12mm Electric Bolt For Fully Frameless Glass Door |
| Signal Output       | Door Status Output,NO/COM                         |
| Surface Temp        | Low Temperature                                   |
| Induction Distance  | 8mm   |
| Operating temp      | -10~+55°C(14-131F)                                |
| Operating Humidity  | 0~90%(non-condensing)                             |
| Special Designed    | Tested to 500000 operations                       |
| Face place material | Stainless Steel                                   |
| Weight              | 1.8kg   |

