[illegible] / [illegible] [illegible]-[illegible] **3-6** [illegible]

[[illegible], [illegible] [illegible] & [illegible], [illegible] [illegible] & [illegible]]()

[illegible]:
[illegible]: [illegible],MIFARE® [illegible], [illegible], [illegible] ([illegible])
[illegible]
[illegible]: 120 [illegible] 120 [illegible]
[illegible]
[illegible]
[illegible]
[illegible] modularized [illegible]
[illegible] 3080[illegible]
[illegible] (4.8 [illegible])
[illegible]

[illegible]:

[illegible]	PY-U3-6
[illegible] - [illegible]	0.3[illegible], [illegible] CMOS
[illegible]	500 [illegible]
[illegible]	[illegible] 20 [illegible] 4H [illegible] 1000 [illegible]
[illegible]	& LT; 1 [illegible]
[illegible]	1: [illegible]
FRR	≤1%
[illegible]	≤0.0001%
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible] 120 [illegible]
[illegible]	& Lt; 20UA ([illegible]) & Lt; 120UA ([illegible]) & Lt; 220UA ([illegible])
[illegible]	& LT; 200mA
[illegible]	4 [illegible], [illegible] 6V
[illegible]	[illegible] 10, 000 [illegible]
[illegible]	4 [illegible] / 6V ~ 9Vexternal [illegible]
[illegible]	-10 [illegible] ~ 55 [illegible]
[illegible]	& LT; 4.5V

[illegible]:
[[illegible]]()

ADEL
ADEL