

7 " PY-V812MC13

Features:

- 1 year warranty
- 3 years of free technical support
- 7 "(16: 9) TFT LCD display
- 1/3 "CMOS sensor
- 16: 9 aspect ratio
- 24 hours of continuous operation
- 1.1W power consumption

Specifications:

- 7 "TFT LCD display (16: 9) resolution: 480 X 234 pixels
- Brightness: 250cd / m<sup>2</sup>
- Aspect ratio: 16: 9 / NTSC
- Viewing angle: - 50 degrees (horizontal) - 70 degrees (vertical)
- Contrast ratio: - (white to black) 200: 1 - (white to grey) 50: 1
- Talkbacking: 120 pixels ± 10%
- Response time: 60 pixels ± 10%
- Resolution: 16 pixels
- Temperature range: -10 degrees Celsius ~ 50 degrees Celsius
- Humidity range: -30% ~ 80%
- Power consumption: 10% ~ 90%
- Power supply: 56db
- Input voltage: - 100 ~ 240V, 0.5A (AC) - Output: 15V, 1.2A
- Dimensions: 250 (mm) x 150 (mm) x 26 (mm)
- Weight: 1.1kg

General:

- 1/3 "CMOS sensor
- Aspect ratio: 16: 9 / NTSC
- Resolution: - 420TVL- resolution: 628 X 582 pixels- NTSC resolution: 510 X 492 pixels
- Brightness: 3.6 cd/m<sup>2</sup>
- Response time: 5 pixels, 10 pixels
- Viewing angle: - 66 degrees (horizontal) - 75 degrees (vertical)
- Power consumption: 1.1W
- Operating temperature: 4m / 13ft
- Storage temperature: -10 degrees Celsius ~ 50 degrees Celsius
- Operating temperature: -40 degrees Celsius ~ 85 degrees Celsius
- Power supply: (AC) 15V
- Dimensions: - 88 (mm) x 180 (mm) x 35 (mm)
- Weight: - 93 (mm) x 185 (mm) x 40 (mm)
- Weight: 1.1kg

□□□□□□ □□□□□□ □□□□□□□□□□:

□□□□□ □□□□ □□□□□□□ □□ □□□□□□□: 4 □□□

□□□□□ □□□ □□□□ □□ □□□ □□□□ □□□□□□□: 2-□□□