

7 " PY-V812MC13

Features:

- 1 year warranty
- 3 years free on-site service
- 7 "(16: 9) TFT LCD display
- 1/3 "CMOS sensor
- 16: 9 aspect ratio
- 24 hours operation
- 1.1W power consumption

Specifications:

- Screen: 7 "TFT LCD (16: 9) resolution: 480 X 234 pixels
- Brightness: 250cd / m²
- Aspect ratio: 16: 9 / NTSC
- Viewing angle: - 50 degrees (horizontal) - 70 degrees (vertical)
- Contrast: - (white to black) 200: 1 - (white to grey) 50: 1
- Talkbacking: 120 pixels ± 10%
- Response time: 60 ms ± 10%
- Pixel pitch: 16 micrometers
- Ambient light: -10 lux ~ 50 lux
- Temperature: -30 degrees ~ 80 degrees
- Humidity: 10% ~ 90%
- Power consumption: 56db
- Input: 100 ~ 240V, 0.5A - Output: 15V, 1.2A
- Dimensions: 250 (mm) x 150 (mm) x 26 (mm)
- Weight: 1.1kg

General:

- Sensor: 1/3 "CMOS
- Aspect ratio: 16: 9 / NTSC
- Resolution: - 420TVL- resolution: 628 X 582 pixels- NTSC resolution: 510 X 492 pixels
- Frame rate: 3.6 frames
- Shutter speed: 5 frames, 10 frames
- Viewing angle: - 66 degrees (horizontal) - 75 degrees (vertical)
- Lens: 4m / 13ft
- Temperature: -10 degrees ~ 50 degrees
- Temperature: -40 degrees ~ 85 degrees
- Power: 15V
- Dimensions: 88 (mm) x 180 (mm) x 35 (mm)
- Weight: 93 (mm) x 185 (mm) x 40 (mm)
- Weight: 1.1kg

□□□□□□ □□□□□□ □□□□□□□□□□:

□□□□□ □□□□ □□□□□□□ □□ □□□□□□□: 4 □□□

□□□□□ □□□ □□□□ □□ □□□ □□□□ □□□□□□□: 2-□□□