

□□□□ □□□□ □□□□ □□□□□□ □□□:

- : □□□□ □□□□ □□ □□□ MIFARE® □□□□□□, (□□□□□□□ □□□□□□ □□□□□□□□□□ □□ □□□□□□□□□□)
- : TEMIC □□□□□□ □□□□□□□□□□, (□□□□□□□ □□□□□□ □□□□□□□□□□ □□ □□□□□□□□□□)
- : □□□□ □□□□□□□□□□, (□□□□□□□ □□□□□□□□□□□□, □□□□ □□□□□□□□ □□□□□□□□□□□□)

□□□□□□ □□□□□□ □□ □□□□□□□□ □□□ □□ □□□□□□ □□□□□□□□□□

- 1□ □□ □□□□ □□□□□□□□ □□ □□□□□□□ □□□□□□□ □□ □□□ □□ □□□ zink □□□□□□ □□□□□□ (□□□□□□□□□ □□□□□□ □□ □□□□□□) □□ □□□□ □□□□
- 2□ □□□□□□□ □□ ntellectual □□□□□□□□ □□□□□ □□□□□ □□□□, □□ □□□ □□□□□ □□□ □□□□ □□ □□□ □□□ □□□□□□ □□ □□□□□□ □□□□□□ □□□□
- 3□ □□: □□□□□□ □□□□□□□, □□□□□□□ □□□□□□□ □□ □□□□□□ □□ □□ □□□□□□ □□□□□ □□ □□□□□ □□ □□□□□ □□□ □□□□ □□□□ □□□□ □□□□ □□□□
- 4□ □□ □□□□ □□□□□ □□ □□□□□□□□□□ □□□□ □□ □□□ □□ □□□□□□ □□□□□□ □□ □□□□□□□□ □□□□□□□□ □□□□□□□□ □□□□□□

□□□□□□ □□□□□□□□:

Working voltage	6.0V (4 pieces of No.5 alkaline batteries)
Static current	≤15 μA
Card reading current	≤20 mA
Lifespan of batteries	10 months or above
Indication of lacking voltage	4.8V
Induction distance	>25mm
Working temprature	-20`C~70`C
Working humidity:	≤80%

□□□□□□ □□□□□□ □□□□□□□□ □□□□ □□□□□ □□□□□□□□ □□□□□



RF card



RF card reader
(used for issuing room card to guests)



Data collector



opening the door with RF card



collect opening records from hotel lock

proyu.en.alibaba.com