


□□□□□□ □□□□ □□□□□□□□□□□□ □□□ □□□□:

- : □□□□ □□□□ □□ □□□ MIFARE® □□□□□□,
- : □□□□□□ □□□□□□ □□□□ □□□□
- : □□□ □□□□□ □□□

□□□□□□ □□□□□□□□□□□□□□ □□□ □□ □□□□□ □□□□□□□□□□

1. □□ □□ □□□ □□□□□ □□□□□ □□□□□ (□□□□□□□□□ □□□□□ □□ □□□□□□) □□□□□□ □□□□□ □□□□ □□, □□□□ □□□□□□□ □□ □□□□□□ □□□□□□□□ □□ □□□□
2. □□□□□□□ □□□□□□□ □□□□ □□□□□ □□□□□, □□ □□□ □□□□□ □□ □□□ □□ □□□ □□□ □□ □□□ □□□ □□ □□□ □□ □□□ □□ □□□ □□ □□□ □□□□□ □□ □□□□□ □□□□□ □□□□
3. □□□□□□ □□□□□□ □□ □□□□□□ □□□□ □□ □□□□□ □□□□ □□ □□□□□ □□ □□□□ □□ □□□ □□: □□□□□□ □□□□□□□ □□□□□□ □□□□ □□□□ □□
4. □□ □□□□ □□□□ □□ □□□□□□□□□ □□□□ □□ □□□ □□□□□□□□ □□□□□□ □□□□□ □□ □□□□□□□ □□□□ □□□ □□□□□□
5. □□□□□□ □□□□□□□□□□ □□ □□□ □□□□□□□ □□□□□ □□ □□□□ □□□ □□□ □□□ □□□□□ □□□□□ □□□□□□

□□□□ □□□□□□□ □□□□ □□□□□ □□□□□ □□□□ □□□□□□□□□□□□ □□□□



□□□□□ □□□□□□ □□□□ □□□□□□ □□□□□□□□□□□□ □□□ □□ □□□ □□□□ □□□□□



Specifications:

Operating Voltage	6.0V (5 pin or 4 pin)
Operating Current	& LT; 15µA
Operating Power	≤20µA
Operating Temperature	10 pin or more
Operating Time	4.8V
Operating Mode	& Gt; 25mm
Operating Range	-20°C ~ 70°C
Operating Accuracy	≤80%

Application:

- ... ( ... ), ... , ... , ... , ...
- ...
- ...
- ...
- ...
- ...



**RF card**



**RF card reader**  
(used for issuing room card to guests)



**Data collector**



opening the door with RF card



collect opening records from hotel lock