

RFID 卡片的規格與應用 -5500

規格: 13.56MHz, ISO 15693, MIFARE® 1K, MIFARE® 4K, MIFARE® 10K, MIFARE® 16K, MIFARE® 2K, MIFARE® 3K, MIFARE® 7K, MIFARE® 8K, MIFARE® 9K, MIFARE® 10K, MIFARE® 16K, MIFARE® 2K, MIFARE® 3K, MIFARE® 7K, MIFARE® 8K, MIFARE® 9K

規格:

- 晶片型號: MIFARE® 晶片
- 晶片尺寸: 8.5mm x 25mm
- 晶片厚度: 1.2mm
- 晶片重量: 0.5g
- 晶片電壓: 3V
- 晶片電流: 10mA
- 晶片溫度: 0°C ~ 70°C
- 晶片壽命: ≥ 100,000 次
- 晶片讀取距離: ≤ 10cm
- 晶片寫入距離: ≤ 10cm
- 晶片擦除距離: ≤ 10cm
- 晶片加密: AES-128
- 晶片認證: MIFARE® 認證

規格:

工作電壓: 6.0V (5V ~ 6.0V)

工作電流: < 100µA

最大電流: < 200mA

工作溫度: 0°C ~ 70°C

工作濕度: ≤ 80%

規格:

● Part Name



Part Name:

1. Hexagonal screw (M3*8)
2. Cylinder
3. Battery cover
4. Handle
5. Front lock assembly
6. Door
7. Square shaft
8. Back lock assembly
9. Fixing screw (M5)
10. Screw cover
11. Cylinder fixing screw (M5*70)
12. Wood screw (M4*25)
13. Mortise







