

Facial and Card Identification Terminal with High Definition Infrared Camera PY- iface301

Parameters:

CPU	Branded Multi-Bio CPU 630 MHz
Memory	256M Flash, 64M SDRAM
Hardware Platform	ZEM600 Multi-Medium Development Platform
Fingerprint Sensor	None
Camera	High Resolution Infrared Camera
Display	4.3" TFT touch screen
Face capacity	400 (1:N)
Fingerprint capacity	None
ID Card capacity	10,000
Logs capacity	100,000
Algorithm Version	Branded Face 7.0
2000mAh backup battery	Optional
Communication	TCP/IP,RS232/485
USB-HOST	Two USB-Host
Wireless Wi-Fi	Optional
Time attendance Standard functions	ID Card(302 Optional), Automatic Status Switch, Self-Service Query, Work Code, T9 input, 9 digit user ID, DLST
Access control interfaces for	3rd party electric lock, door sensor, exit button
Wiegand Signal	Output
Optional functions	serial printer, other rf card, Extendable Scheduled-bell, Short Massage, Web-server, GPRS
Power supply	12V3A
Verification Speed	≤2 sec
Operating temp	0°C- 45 °C
Operating Humidity	20%-80%
Dimension	193.6*146.8*111 mm (Length*Width*Thickness)
OEM	Yes
SDK	Available
Multi languages	Available
bell scheduling	Built in
Serial and Ethernet ports	Build in

Application: home, office, school, government, building , or other purpose