

Home Security Intercom System 7" LCD Video Door Phone Kit Support 3 Families PY-V812MC13

Features:

This package includes 3 Indoor Monitors + 1 Outdoor Camera
Specially designed for 3 families, it absolutely can fully meet 2 families' needs
7" (16:9) TFT LCD Screen
1/3" CMOS outdoor camera
High quality dual-way audio communication
Outdoor monitoring function
Do not disturb mode
Infrared night vision supported
Hands-free intercom
Electronically unlocking control
24 kinds of polyphonic chord ringtones
Low standby power consumption: <1.1W

Technical Parameters:

Indoor Monitor

Screen :7" TFT LCD (16 : 9)Resolution :480 x 234 pixels
Brightness :250cd / m²
Standard : PAL / NTSC
Viewing Angle :- approx. 50° (Up)- approx. 70° (Down, Left, Right)
Effective Distance :- up to 200m (between indoor and outdoor unit)- up to 50m (between indoor and extra indoor unit)
Talkbacking Time : 120 sec ± 10%
Monitoring Time :60 sec ± 10%
Polyphonic Chord Ringtones : 16 types
Operating Temperature : -10°C ~ 50°C
Storage Temperature : -30°C ~ 80°C
Relative Humidity : 10% ~ 90%
Microphone Sensitivity : 56db
Power Supply : - Input : AC 100~240V, 0.5A (worldwide voltage)- Output : DC 15V, 1.2A
Dimensions : - Approx. 250 (W) x 150(H) x26 (D) mm
Installation Method : Wall-mounted

Outdoor Camera

Image Sensor :1/3" CMOS
Standard : PAL / NTSC
Resolution : - 420TVL- PAL : 628 x 582 pixels- NTSC : 510 x 492 pixels
Focal Length : 3.6mm
IR LED : 5 pcs, 10 Lux
Visual Angle :- approx. 66° (Up, Down)- approx. 75° (Left, Right)
Gain Control : Auto
Infrared Night Vision Distance : Approx. 4m / 13ft
Operating Temperature : -10°C ~ 50°C
Storage Temperature : -40°C ~ 85°C
Power Supply : DC 15V (directly powered by indoor monitor)
Dimensions : - Approx. 88 (W) x 180 (H) x 35 (D) mm
Dimensions (with rain cover) : - Approx. 93 (W) x 185 (H) x 40 (D) mm
Installation Method : Wall-mounted

Installation Cables Requirement:

Monitor to Camera Connection Cable :4-pin

Camera to Lock Connection Cable : 2-pin