## Metal Pin-hole Camera 7" TFT Color Video Doorphone Building Intercom System PY-V7E-M

## **Products Features:**

- ♦Pieces of metal at the gate of pin-hole machine, classic humanized design, CMOS or CCD camera.
- Hands-free type indoor unit, classic styling, 7 inches of true color TFT. Clear images
- ♦Intercom, monitoring, communication, the lock function
- ♦Night vision and inside the intercom function. (more than one indoor unit)
- ♦Pieces of image brightness, color, adjustable ring ring tone.
- A variety of chord ring are free to switch, elegant and pleasing to the ear.

◆In pieces the outdoor unit and indoor unit free form a complete set of 1 to 4, 2 to 4, etc., and meet the demand of different users,

♦International standard design and production, four wire system, simple and convenient installation, the user can install itself.

♦Mixer is suitable for the villa, family, office, office buildings, office, etc.

## **Products Parameters:**

- Audio mixer boomed with 50 mw or higher
- ◆Talking time: 90 seconds, monitoring time: 30 seconds
- ◆The power adapter input voltage: AC100-240V 50hz-60hz
- ◆The power adapter output voltage: AC14.5 V 1200 ma
- ♦Frequency response: 300~3400hz +/±3dB
- ♦Working voltage: DC15V plus or minus 10%
- Resolution: 200000 pixels
- $\bullet$ Power consumption: static <0.5 W, phone state <10 W
- Installation method: the outdoor unit embedded installation, indoor unit hanging from the handle
- Indoor machine overall size: 225 (long) x 168 (width) x 29 mm (thickness)
- ◆The door machine appearance size: 69 (long) x 157 (width) x 23 (thick) in mm
- ♦Installation dimensions: 49 (long) x 126 (width) x 20 mm (thickness)

## Wiring Requirements:

- ♦30 meters: RVV4 (4 core) x 0.5 mm
- ♦50 meters: RVV4 (4 core) x 0.75 mm
- ♦100 meters: RVV4 (4 core) x 1.0 mm