

Frameless glass doors up and down power plug lock

Features:

- * Low Temperature, safe & Durable
- * Low Power, Environmental Protection
- * Special photo electricity control,three steps current application
- * Long Life with 500000 Operations
- * MOV Provides Reverse Current Protection
- * Superior Strength Aluminium Alloy,Solid Stain-less Steel Bolt
- * Autolock Time Delay: 0,3,6,9sec.
- * Door statue signal output contact(NC.COM)
- * Double protection for loading current
- * Auto-relock if no Action within 5 secs.
- * Photoelectricity Control,Low Temperature,
A:The Low Current is Changed immediately;
B:When door frame doesn't coincide with door leaf ,door leaf against the bolt,then the electric bolt will start the low-power function to bring low temperature.

C:The Photoelectricity Control Technology, prevent the machanical defect.

Technical Specifications:

| | |
|---------------------|---|
| Place of Origin | Guangdong, China (Mainland) |
| Brand Name | Proyu |
| Model Number | PY-EL8 |
| Fail Safe | Lock when energized |
| Face Plate | L148xW43xH39(mm) |
| Bolt | 17mmDIA,stainless steel 13mm throw |
| Voltage | DC12V(DC24V) |
| Start Current | 900mA |
| Standby Current | 120mA |
| Support Grip | 400kg |
| Suitable For | 12mm Electric Bolt For Fully Frameless Glass Door |
| Signal Output | Door Status Output,NO/COM |
| Surface Temp | Low Temperature |
| Induction Distance | 8mm |
| Operating temp | -10~+55°C(14-131F) |
| Operating Humidity | 0~90%(non-condensing) |
| Special Designed | Tested to 500000 operations |
| Face place material | Stainless Steel |
| Weight | 1.8kg |

