[illegible] RFID [illegible] PY-CR31

[illegible]

- 125KHz MIFAREï[illegible] Proximity Card Reader
- [illegible]: [illegible] 10CM (125KHz) / 5CM (MIFAREï[illegible])
- 26 / 34bit Wiegand ([illegible])
- [illegible]
- [illegible] LED [illegible]
- [illegible] Buzzer [illegible]
- [illegible] / [illegible]
- [illegible]
- [illegible] IP65
- [illegible]

[illegible]:

[illegible]	EM	
[illegible]	[illegible] 10 [illegible]	
[illegible] ([illegible])	≤300ms	
[illegible] / [illegible]	DC 6-14V / Max.70mA	
Input Port	2 [illegible] ([illegible] LED [illegible] Buzzer Control)	
[illegible]	26bit Wiegand ([illegible])	34bit Wiegand ([illegible])
[illegible] LED	2 [illegible] LED [illegible] ([illegible])	
Beeper	[illegible]	
[illegible]	-20 °[illegible] + 65 ° C	
[illegible]	10% [illegible] 90% [illegible]	
[illegible]	[illegible]	
[illegible]	ABS + PC [illegible]	
[illegible] ([illegible] x [illegible] x [illegible]) [illegible]	84.5 * 44 * 16.8	
[illegible]	55g	
[illegible]	IP65	

[illegible]

[illegible] DC 5V-16V

[illegible] GND

[illegible] D1

[illegible] D0

[illegible]

LED [illegible]

[illegible]