[illegible] biometric [illegible] / [illegible] PY-U3-6

[illegible]:

[illegible]: [illegible],[illegible]MIFARE®, [illegible], [illegible] ([illegible])

Keyless [illegible]

[illegible]

[illegible]: 120 [illegible]

[illegible]

[illegible]

[illegible]

[illegible] modularized

[illegible] 3080UV

[illegible] ([illegible] 4.8V)

[illegible]

[illegible]

[illegible]:

[illegible]	PY-U3-6
[illegible]	0.3 [illegible] CMOS
[illegible]	500 DPI
[illegible]	[illegible] 1000 [illegible] 4 [illegible] 20 [illegible]
[illegible]	& lt; 1 [illegible]
[illegible]	1: N
FRR	≤1%
FAR	≤0.0001%
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible] 120 [illegible]
[illegible]	& lt; 20UA ([illegible]) & lt; 120UA ([illegible]) & lt; 220UA ([illegible])
[illegible]	& lt; 200mA
[illegible]	[illegible] AA alkaline 4 [illegible], DC 6V
[illegible]	[illegible] 10,000 [illegible]
[illegible]	[illegible] AA alkaline 4 [illegible] / [illegible] 6V ~ 9Vexternal
[illegible]	-10 ° C ~ 55 ° C
[illegible]	& lt; 4.5V

[illegible]:

[illegible]

ADEL
ADEL