RF [illegible]:

: Mifare ®[illegible] ([illegible] USB [illegible])
B: [illegible] Temic ([illegible] USB [illegible])
C: EM [illegible] ([illegible])

[illegible]

1 [illegible] Zink ([illegible]) [illegible]

2 [illegible]ntellectual [illegible]

3 [illegible]

4 [illegible]

[illegible]**:**

Working voltage	6.0V (4 pieces of No.5 alkaline batteries)
Static current	≤15 μA
Card reading current	≤20 mA
Lifespan of batteries	10 months or above
Indication of lacking voltage	4.8V
Induction distance	>25mm
Working temprature	-20`C~70`C
Working humidity:	≤80%

[illegible]


13
12
14
11
9
8
3
a
b
c
5
2
1
6
4
17
10
15
16
Here's two arrows pointing the direction to be horizontal, and the lock cylinder cover on the arrow on the upper, non-vertical point!
Attention! ! !

□□□□□□□□□□□□□□□□□□□□□□□□□□□□

EC Certificate of Conformity

Verification of Conformity

Certificate of Conformity
RoHS

□□□□□□□□□□□ □ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

LOCK □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

- □□□□□□□□□□ (□□□□□□□□□□□□□□□□□), □□□□□□□□□□, □□□□, □□□□□□□□□□ one.Also □□□□□□□□□□□□□□□ □□□□□□□□□□□□□, □□□□□□□□□□□□ system..as □□□□□□□□□□□□□□□□□□□□

- □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

- □□□ easily..and □□□ □□□□□□□□□□□□□□□□□□□□□□, □□

- □□□ □□□

- □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ / □□□□□□□ / □□□□□□□□□□□□□□□□□□□□□□

- □□□ □

RF card

RF card reader
(used for issuing room card to guests)

Data collector

opening the door with RF card

collect opening records from hotel lock

proyu.en.alibaba.com