

1. 7
 2. PY-V806MJM11

1.

- 2.4 G
- 300
- 7 TFT
- 0.3Mega
- Nightvision 24
- 
- 
- 
- 
- 100
- 16

1.

- |                                |  |
|--------------------------------|--|
| 7 TFT                          |  |
| PAL/NTSC                       |  |
| 960 * 480                      |  |
| 90dBm                          |  |
| 250mA                          |  |
| 20-30mA / 3.7 v                |  |
|                                |  |
| 1350mah                        |  |
|                                |  |
| 120                            |  |
| AC100 ~ 240V 50 / 60Hz DC5V/1A |  |
| 6W                             |  |
| 300                            |  |
| -10° C ~ + 50° C               |  |
| -20° C~ + 60° C                |  |
| 85%                            |  |
| 22.5 * 12.8 * 2.3              |  |

1. CameraTechnical

- |                               |     |
|-------------------------------|-----|
| 1/4 CMOS OV7725               |     |
| PAL: 628 * 582 NTSC:510 * 492 |     |
| > 420                         |     |
| PAL/NTSC                      |     |
| Focus(mm)                     | 3.6 |
| 92                            |     |
|                               |     |
| 1350mah                       |     |
|                               |     |
| 2                             |     |
| AC100 ~ 240V 50 / 60Hz        |     |
| DC5V/1A                       |     |

1. 规格: 2W  
 2. 尺寸: (H) 168×(W) 110×(D) 65 mm.

3. 包装清单:
- 1 \* 充电器
  - 1 \* 数据线
  - 1 \* 说明书
  - 1 \* 保修卡
  - 2 \* 螺丝
  - 1 \* USB
  - 1 \* 配件包
  - 1 \* 说明书 - 电子版